

Best[®]
Theratronics



Raycell[®] Mk1
X-ray Blood Irradiator

Technical Specifications

Weight		Photon Energy
550 kg (1200 lbs)		160 keV max, 60–80 keV average
Floor Loading		Cooling System
70 kg/cm ² (1000 lbs/in ²)		Self-contained cooling system — no external water required
Dimensions		Electrical Requirements
Height	1255 mm (49.4 in)	Single-phase 60Hz, 21A typically at 208V
Width	1060 mm (41.75 in)	Single-phase 50Hz, 19A typically at 230V
Depth with UPS	975 mm (38.4 in)	Environmental Requirements
Depth without UPS	870 mm (34.25 in)	Temperature: 10°–30°C (50°–86°F); Relative Humidity: 5%–75%

Canister Features	
Volume	1.7 L
Diameter	173 mm (6.8 in)
Height	79 mm (3.1 in)
Estimated Number of Bags per Cycle	3 Bags, 300 ml each
Central Dose Rate	~6.3 Gy/min
Time for 25 Gy Central Dose	~4 min
Dose Uniformity	19.6 to 34.3 Gy (1.75:1)
Time for 25 Gy Minimum Dose	~5 min
Dose Uniformity	25 to 43.8 Gy (1.75:1)

Options & Accessories
Barcode Reader
Syringe Holder
LIMS Connection
Printer Connection
Additional Canisters
Irradiation Verification Indicators
Service Agreements
Dosimetry
UPS

Pending 510(k) approval

BT/MF 8017 RCMK1 (1) v.09.2017

Best Theratronics 413 March Road, Ottawa, ON K2K 0E4 Canada
 phone 613 591 2100 fax 613 591 6627 www.theratronics.ca www.teambest.com

AFRICA | ASIA | EUROPE | LATIN AMERICA | MIDDLE EAST | NORTH AMERICA

© 2017 Best Theratronics. All Rights Reserved. The specifications contained in this brochure are subject to change.

